



**1. Attach bracket to shower arm**  
 1. Fije el soporte al brazo de ducha  
 1. Fixer le support au bras de douche

**2. Attach Hex-Coupler to bracket**  
 2. Fije el acoplador hexagonal al soporte  
 2. Fixez le coupleur hexagonal au support

**3. Attach conical-coupler to filter handle**  
 3. Acoplar el acoplador cónico para filtrar el mango  
 3. Fixer le coupleur conique filtrer la poignée

## INSTALLATION

1. Remove the existing shower head from the shower arm pipe. Clean the shower arm threads with a soft brush.
2. Hand tighten the shower arm hose-bracket onto the threaded shower arm pipe.
3. If leakage occurs, wrap the shower arm pipe threads with Teflon tape.
4. Insert rubber washers into each end of the hose.
5. Tighten the hose hexagonal end coupler onto the shower arm hose bracket.
6. Hand tighten the hose conical end coupler onto the threaded shower handle.
7. Place the conical end coupler into shower arm bracket holder.

## OPERATION

### BEFORE ENTERING THE SHOWER

1. Activate filter by running hot water through the filtered shower handle for 1 minute before using.

### 2. COOL TO DESIRED TEMPERATURE BEFORE ENTERING SHOWER

## MAINTENANCE

1. Reverse the filter cartridge every month to ensure maximum filtration performance and water flow.
2. Replace the filter cartridge (model HHC) every 3 months or 5,000 gallons, whichever comes first.

## FILTER CARTRIDGE REPLACEMENT (MODEL HHC)

### FOR SCREW-ON TYPE OF HANDLE:

1. To Open: Unscrew the handle from the neck of the shower head.
2. Remove the used filter cartridge.
3. Lubricate the O-rings of the new filter cartridge with petroleum jelly.
3. Insert the new filter cartridge into handle.
4. To Close: Hand-tighten the handle onto the neck of the shower head.

### FOR TWIST-LOCK TYPE OF HANDLE:

1. To open: Turn the handle counter-clockwise and pull away from the showerhead. (twist off and pull)
2. Remove the used filter cartridge.
3. Lubricate the O-rings of the new filter cartridge with petroleum jelly.
3. Insert the new filter cartridge into handle.
4. To close: Insert the handle into the neck of the shower head and twist clockwise until locked into position. (push and twist on)



1791 Railroad St., Corona, CA 92880 U.S.  
**Phone:** 800-327-9137 (US Toll Free)  
 or 951-735-1015

1791 Railroad St, Corona, CA 92880 EE. UU.  
**Teléfono:** 800-327-9137 (gratis en EE. UU.)  
 o 951-735-1015

1791 Railroad St, Corona, CA 92880 États-Unis  
**Téléphone:** 800-327-9137 (appel gratuit)  
 ou 951-735-1015



## USE & CARE INSTRUCTIONS

# Filtered Shower Handle

## Instrucciones de uso y cuidado ASA DE DUCHA FILTRADO

## Instructions d'utilisation et d'entretien POIGNÉE DE DOUCHE FILTRÉE

## PERFORMANCE DATA: MODEL HHC FILTER CARTRIDGE

**Maximum Rated Service Flow** –  
 2.5 gallons per minute /  
 9.5 liters per minute

**Maximum Rated Service Life  
 for Free Chlorine removal** –  
 3 months or 5,000 gallons /  
 18,927 liters (whichever comes first)

**Maximum Working Pressure** –  
 125 pounds per square inch /  
 861 kilo pascals.

**Maximum Operating Temperature** –  
 120° Fahrenheit / 49° Celsius.

- While testing was performed under laboratory conditions. Actual performance may vary.

### NOTE:

- This system is not intended to be used as a drinking water treatment unit.
- Both the system and installation must comply with applicable state and local regulations.

This Sprite Shower Filtration System has been tested for reduction of free chlorine. The concentration of free available chlorine in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system. This system has not been evaluated for free chlorine reduction in the presence of chloramines. Free chlorine reduction performance may be impacted by the presence of chloramines in the water supply.

## LIMITED ONE YEAR WARRANTY

Sprite Industries, Inc. warrants the Filtered Shower Handle housing only (not the cartridge) to be free of defects for a period of one (1) year when used under normal operating conditions. At the time of purchase, it is the owner's responsibility to complete the product warranty information available on-line at [www.spriteshowers.com](http://www.spriteshowers.com), to keep proof of purchase of the unit and all replacement cartridge(s) and to document that proper cartridge replacement and filter maintenance was performed as specified in the owner's instructions. The provisions of this warranty shall not apply to any product that has been submitted to: misuse, neglect, over-tightening, lack of or improper periodic filter replacement, repaired or altered by anyone other than an authorized Sprite Industries service representative, and will VOID the warranty in its entirety. Transportation costs for units submitted for repair or replacement under warranty to Sprite Industries, Inc., 1791 Railroad Street, Corona CA 92880-2511 shall be paid by the registered owner. This is exclusive remedy and liability for consequential damages. There are no other warranties, expressed or implied, limited to the extent permitted by law.

## FOR MORE INFORMATION AND ON-LINE REGISTRATION

Go to: [www.spriteshowers.com](http://www.spriteshowers.com)